

TDS - SEAL 2522 HSP

PRINTED PACKAGING TAPE FOR LIGHT/MEDIUM DUTY APPLICATIONS

PRODUCT DESCRIPTION:

Bock SEAL 2522 HSP is a 45µm printed superior performance carton sealing tape with increased adhesive coating for demanding light to medium duty applications. It is a great solution for reliable all-temperature and all-weather box sealing, requiring excellent clarity and resistance to aging, weathering, UV-light, and yellowing. Its top quality high shear acrylic adhesive guarantees excellent quick stick properties and a superior shear strength.

FEATURES & BENEFITS

- High Initial Tack
- High Shear Strength
- Excellent Resistance to Aging

TYPICAL APPLICATIONS: Best choice for sealing recycled corrugated boxes and other packaging applications. Used for packaging, bundling, and for packages exposed to challenging shipping hazards and stress.

PROPERTIES

Adhesive System	High Shear Acrylic Emulsion
Backing	BOPP Film
Backing Thickness	25µm
Adhesive Coating	22 GSM
Total Thickness	46µm
Country of Origin	India
Core Diameter	76.2mm
Available Sizes	hand rolls/machine rolls
Colors/print	Clear/Colored/Printed



TECHNICAL DATA

Property	Nominal Value	Norm
Elongation at Break	>100%	ASTM D3759
Tensile Strength	7.7Kg/cm ²	ASTM D3759
Adhesion to Steel	>2.1N/cm	ASTM D3330
Shear Strength (Paper)	125min	ASTM D3654
Rolling Ball Tack	6-9 cm	ASTM D3121-06
Application Range	+10°C - +60°C	
Operating Range	-20°C - +60°C	

ADDITIONAL INFORMATION

Customization: Bock SEAL 2522 HSP is available in transparent, solid colors and custom printed version. Please contact your sales representative for more information.

Storage & Shelf Life: It is good practice to use the product within 12 months from purchase date. The rolls must be kept in their original packaging. Keep the product out of the light and protect it from direct heat sources. The tape must be kept in a dry place, at a humidity level below 65%, preferably at a temperature between 15° C and 25° C. If the storage temperature is different, restore the tape back to above level before using it.

TDS - SEAL 2522 HSP

This Technical Data Sheet (TDS) is provided by BOCK for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. BOCK expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. BOCK does not exclude liability for death or personal injury arising from its negligence or fraud. BOCK refers to Bock Middle East FZCO and its subsidiaries.

