

## TDS - TAPE PRO 1060

### PREMIUM HIGH TEMPERATURE INDUSTRIAL GRADE MASKING TAPE

#### PRODUCT DESCRIPTION:

TAPE PRO 1060 is a 110°C high temperature masking tape for automotive and industrial painting and coating applications. It sticks to a wide variety of surfaces, stays positioned, and can be removed without leaving glue residue. It's high temperature resistance, very easy unwind and high conformability makes it the perfect choice for pipe coating applications.

#### FEATURES & BENEFITS

- Easy Unwind
- High Temperature Resistance
- Easy & Clean Removal

**TYPICAL APPLICATIONS:** Best choice for all masking applications where high temperature resistance and high conformability are required.

#### PROPERTIES

Adhesive System	Natural Rubber
Backing	Semi-Crepe Paper
Paper Weight	65g/m <sup>2</sup>
Total Thickness	139µm
Color	Ivory
Country of Origin	Italy
Core Diameter	76.2mm
Available Sizes	24mm, 48mm, 75mm
Length	50m



#### TECHNICAL DATA

Property	Nominal Value	Norm
Elongation at Break	7%	ASTM D3759
Tensile Strength	4Kg/cm	ASTM D3759
Adhesion to Steel	250g/cm	ASTM D3330
Rolling Ball Tack	1 cm	ASTM D3121-06
Temperature Resistance	+100°C (60min)	
Removal Time	5 days Indoor	

#### ADDITIONAL INFORMATION

**Customization:** Aside from the standard widths and lengths, Bock TAPE PRO 1060 can be supplied as well in various other dimensions, based on the need of the applicator. Please reach out to our sales representatives to develop the customized solution for your needs.

**Storage & Shelf Life:** It is good practice to use the product within 12 months from purchase date. The rolls must be kept in their original packaging. Keep the product out of the light and protect it from direct heat sources. The tape must be kept in a dry place, at a humidity level below 65%, preferably at a temperature between 15° C and 25° C. If the storage temperature is different, restore the tape back to above level before using it.

#### TDS - TAPE PRO 1060

This Technical Data Sheet (TDS) is provided by BOCK for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. BOCK expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. BOCK does not exclude liability for death or personal injury arising from its negligence or fraud. BOCK refers to Bock Middle East FZCO and its subsidiaries.

