

TDS - TAPE PRO 630

PREMIUM QUALITY MASKING TAPE FOR INTERIOR USE

PRODUCT DESCRIPTION:

BOCK TapePRO 630 is a soft 60°C painters masking tape for interior usage. Its soft natural rubber adhesive allows it to stick on a large variety of surfaces while being able to remove without any glue residue even after four days. Our special treated paper does not absorb moisture from the paint and by this guarantees sharp paint lines.

FEATURES & BENEFITS

- Reliable Adhesion
- Residue Free Removal
- Clean and Sharp Paint Lines

TYPICAL APPLICATIONS: TAPE PRO 630

offers excellent performance for decorative painting and other applications. It sticks to a wide variety of surfaces, stays positioned, and gives outstanding clean paint lines

PROPERTIES

Adhesive System	Natural Rubber
Backing	Semi-Crepe Paper
Paper Weight	62g/m ²
Total Thickness	125µm
Color	Ivory
Country of Origin	Italy
Core Diameter	76mm
Available Sizes	24mm, 48mm, 75mm
Length	50m



TECHNICAL DATA

Property	Nominal Value	Norm
Elongation at Break	6%	ASTM D3759
Tensile Strength	3.2Kg/cm	ASTM D3759
Adhesion to Steel	220g/cm	ASTM D3330
Rolling Ball Tack	6 cm	ASTM D3121-06
Temperature Resistance	+60°C (45min)	
Removal Time	3 days Indoor	

ADDITIONAL INFORMATION

Customization: Aside from the standard widths and lengths, Bock TAPE PRO 630 can be supplied as well in various other dimensions, based on the need of the applicator. Please reach out to our sales representatives to develop the customized solution for your needs.

Storage & Shelf Life: It is good practice to use the product within 12 months from purchase date. The rolls must be kept in their original packaging. Keep the product out of the light and protect it from direct heat sources. The tape must be kept in a dry place, at a humidity level below 65%, preferably at a temperature between 15° C and 25° C. If the

TDS - TAPE PRO 630

This Technical Data Sheet (TDS) is provided by BOCK for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. BOCK expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. BOCK does not exclude liability for death or personal injury arising from its negligence or fraud. BOCK refers to Bock Middle East FZCO and its subsidiaries.



storage temperature is different, restore the tape back to above level before using it.

TDS - TAPE PRO 630

This Technical Data Sheet (TDS) is provided by BOCK for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. BOCK expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. BOCK does not exclude liability for death or personal injury arising from its negligence or fraud. BOCK refers to Bock Middle East FZCO and its subsidiaries.

