

## TDS - TAPE PRO 890

### PROFESSIONAL GRADE AUTOMOTIVE MASKING TAPE

#### PRODUCT DESCRIPTION:

TAPE PRO 890 offers top performance for automotive painting jobs and professional contracting applications. It sticks to a wide variety of surfaces, stays positioned, and gives outstanding clean paint lines. TAPE PRO 890 is the solid choice for demanding painting jobs with multiple 80° baking cycles.

#### FEATURES & BENEFITS

- Reliable Adhesion
- Water- & Solvent Based Paints
- Clean Removal

**TYPICAL APPLICATIONS:** TAPE PRO 890 offers excellent performance for demanding automotive applications with multiple baking cycles and removes cleanly even after 2 weeks indoor.

#### PROPERTIES

Adhesive System	Natural Rubber
Backing	Semi-Crepe Paper
Paper Weight	60g/m <sup>2</sup>
Total Thickness	140µm
Color	Orange
Country of Origin	Italy
Core Diameter	76mm
Available Sizes	24mm, 48mm
Length	45yd



#### TECHNICAL DATA

Property	Nominal Value	Norm
Elongation at Break	8 %	ASTM D3759
Tensile Strength	>33 N/cm	ASTM D3759
Adhesion to Steel	> 2.6 N/cm	ASTM D3330
Rolling Ball Tack	1 cm	ASTM D3121-06
Temperature Resistance	+80°C (90min)	
Removal Time	14 days Indoor	

#### ADDITIONAL INFORMATION

**Customization:** Aside from the standard widths and lengths, Bock TAPE PRO 890 can be supplied as well in various other dimensions, based on the need of the applicator. Please reach out to our sales representatives to develop the customized solution for your needs.

**Storage & Shelf Life:** It is good practice to use the product within 12 months from purchase date. The rolls must be kept in their original packaging. Keep the product out of the light and protect it from direct heat sources. The tape must be kept in a dry place, at a humidity level below 65%, preferably at a temperature between 15° C and 25° C. If the storage temperature is different, restore the tape back to above level before using it.

#### TDS - TAPE PRO 890

This Technical Data Sheet (TDS) is provided by BOCK for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. BOCK expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. BOCK does not exclude liability for death or personal injury arising from its negligence or fraud. BOCK refers to Bock Middle East FZCO and its subsidiaries.

